

BATTERY SCRUBBER-DRIER



MOD. 52 BT

| MAIN FEATURES | |
|-------------------------------------|------------|
| Working width | 520 mm |
| Max. working capacity | 2.340 m²/h |
| Solution tank capacity | 50 I |
| Recovery tank capacity | 50 I |
| Max. autonomy (lead-acid batteries) | 2,5-3 h |
| Max. autonomy (gel batteries) | 2-2,5 h |

OTHER FEATURES AND STANDARD SUPPLY Electronic traction - forward/reverse Service and parking brake

Removable filter solution tank Solution tank drain hose with flow adjustment tap Dirty water tank drain hose with flow control Stainless steel squeegee with rubber blades N.1 PPL disk brush

DIMENSIONS AND WEIGHT

| Machine length | 1.460 mm |
|---------------------------------------|----------|
| Machine width (squeegee not included) | 530 mm |
| Machine height | 1.050 mm |
| Brush diameter | 520 mm |
| Squeegee width | 800 mm |
| Machine weight | 88 Kg |

PACKAGING

| Type of packaging | carton box on pallet |
|---------------------|----------------------|
| Dimensions | 1.500x800xH1.250 mm |
| Volume | 1,50 m ³ |
| Weight of packaging | 20 Kg |

| | Ŭ |
|---|--|
| CODE | DESCRIPTION |
| 120052BTV1 | Battery scrubber-drier with electronic traction (forward/reverse)- mod. 52 BT |
| OPTIONAL SUPPLY COEL00001 COEV00001 | Electric digital hour-counter Automatic on/off solution flow control electrovalve |
| BATTERY CHARGERS CB10240120A CB10240150A CB10240121A CB10240121G CB20240121A 3139 | 24V 12A electronic battery charger for lead-acid batteries 24V 15A electronic battery charger for lead-acid batteries (fast charge) 24V 12A electronic high frequency battery charger for lead-acid batteries 24V 12A electronic high frequency battery charger for gel batteries 24V 12A electronic high frequency on-board battery charger for lead-acid batteries 24V 12A electronic high frequency on-board battery charger for lead-acid batteries 24V 12A electronic high frequency on-board battery charger for lead-acid batteries 24V 12A electronic high frequency on-board battery charger for lead-acid batteries |
| BRUSHES COSP515PPLH COSP515ABRH | PPL brush (n.1 unit supplied as standard) Tynex abrasive brush |
| PAD HOLDER/PADS CODT505TRECH 004593 006950 004594 004598 007394 006470 008867 | Pad holder with green pad block included Black pad 20" (510 mm) - supplied in 5 units carton box Brown pad 20" (510 mm) - supplied in 5 units carton box Green pad 20" (510 mm) - supplied in 5 units carton box Red pad 20" (510 mm) - supplied in 5 units carton box Micro-fibre pad 20" (510 mm) Gum pad 20" (510 mm) Sector gum pad 20" (510 mm) |
| SQ. RUBBER BLADES COGU912593P COGU980685 | Squeegee polyurethane blade - front (n.1 unit supplied as standard) Squeegee rubber blade - rear (n.1 unit supplied as standard) |

0-4,5 Km/h 10 % 2.000 mm 36 kg 180 rpm ≤ 68 dB

24 Volt direct current 600 W 24 V DC 600 W 24 V DC 150 W 24 V DC

2 x 12V 110Ah lead-acid - code 850000091 2 x 12V 105Ah gel - code 850000070

СС

GENERAL FEATURES

Max. gradient full load

Brush ground pressure

Brush rotation speed

Depression (H₂O column)

ELECTRICAL SYSTEM

Speed range

Noise level

Voltage

Frequency

Vacuum motor

Traction motor Recommended batteries

Brush motor

120

BA CB

BR со

PA

со