

BATTERY SCRUBBER-DRIER		MOD. FB 65
	MAIN FEATURES Working width 610 mm Solution tank capacity 50 l Recovery tank capacity 50 l Batteries 2x12V 110Ah Max. autonomy 2,5 h	
	OTHER FEATURES AND STANDARD SUPPLY Squeegee with rubber blades Automatic on/off solution flow control electrovalve On-board battery charger 24V 12Ah N.1 PPL disk brush	

GENERAL FEATURES		DIMENSIONS AND WEIGHT	
Speed range	0-4 Km/h	Machine length	1.300 mm
Max. gradient full load	3 %	Machine width (squeegee not included)	710 mm
Depression (H ₂ O column)	107 mBar	Machine height	1.040 mm
Brushes ground pressure	20-40 kg	Brushes diameter	2x305 mm
Noise level	≤ 72 dB	Squeegee width	850 mm
		Machine weight	105 Kg
ELECTRICAL SYSTEM		PACKAGING	
Voltage	24 Volt	Type of packaging	carton box on pallet
Frequency	direct current	Dimensions	1.500x800xH1.150 mm
Vacuum motor	500 W 24 V DC	Volume	1,50 m ³
Brush motor	2 x 300 W 24 V DC	Weight of packaging	20 Kg
Traction motor	1300 W 24 V DC		
Recommended batteries	2 x 12V 110Ah lead-acid - code 850000091 2 x 12V 105Ah gel - code 850000070		

CODE	DESCRIPTION
1200FB65	Battery scrubber-drier - mod. FB65
BATTERY CHARGERS	
CB20240151A	24V 15A electronic high frequency on-board battery charger for lead-acid batteries
CB20240151G	24V 15A electronic high frequency on-board battery charger for gel batteries
BRUSHES	
SZ038	N.2 PPL brushes (n.2 supplied as stand.)
SZ038C	N.2 Tynex abrasive brushes
PAD HOLDER/PADS	
TS046	N.2 pad holders with green pad block incl.
004614	N.2 black pads 13" (330 mm) - supplied in 5 units carton box
010704	N.2 brown pads 13" (330 mm) - supplied in 5 units carton box
008286	N.2 green pads 13" (330 mm) - supplied in 5 units carton box
008288	N.2 red pads 13" (330 mm) - supplied in 5 units carton box
007392	N.2 micro-fibre pads 13" (330 mm)
006465	N.2 gum pads 13" (330 mm)
009585	N.2 sector gum pads 13" (330 mm)
SQ. RUBBER BLADES	
KIT858	Squeegee polyurethane blades - front and rear ones (n.1 kit supplied as standard)