

BATTERY RIDE-ON SCRUBBER-DRIER	MOD. MB 55										
	<p>MAIN FEATURES</p> <table> <tr> <td>Working width</td> <td style="text-align: right;">550 mm</td> </tr> <tr> <td>Max. working capacity</td> <td style="text-align: right;">2.200 m²/h</td> </tr> <tr> <td>Solution tank capacity</td> <td style="text-align: right;">94 l</td> </tr> <tr> <td>Recovery tank capacity</td> <td style="text-align: right;">104 l</td> </tr> <tr> <td>Max. autonomy (lead-acid batteries)</td> <td style="text-align: right;">5 h</td> </tr> </table> <p>OTHER FEATURES AND STANDARD SUPPLY</p> <ul style="list-style-type: none"> Rear traction with differential Dirty water tank drain hose with cap Squeegee with rubber blades Automatic on/off solution flow control electrovalve N.1 PPL disk brush 	Working width	550 mm	Max. working capacity	2.200 m ² /h	Solution tank capacity	94 l	Recovery tank capacity	104 l	Max. autonomy (lead-acid batteries)	5 h
Working width	550 mm										
Max. working capacity	2.200 m ² /h										
Solution tank capacity	94 l										
Recovery tank capacity	104 l										
Max. autonomy (lead-acid batteries)	5 h										

GENERAL FEATURES

Speed range	4 Km/h
Max. gradient full load	8 %
Depression	150 mBar
Noise level	≤ 50 dB

DIMENSIONS AND WEIGHT

Machine length	1.160 mm
Machine width (squeegee not included)	580 mm
Machine height	1.170 mm
Brushes diameter	1x550 mm
Squeegee width	780 mm
Machine weight	100 Kg

ELECTRICAL SYSTEM

Voltage	48 Volt
Frequency	direct current
Vacuum motor	350 W 48 V DC
Brush motor	400 W 48 DC
Traction motor	250 W 48 V DC
Recommended batteries	4 x 12V 90Ah AGM : code 850000022

PACKAGING

Type of packaging	carton box on pallet
Dimensions	1.440x640xH1.330 mm
Volume	1,23 m ³
Weight of packaging	15 Kg

CODE	DESCRIPTION
1200MB55	Battery ride-on scrubber-drier - mod. MB55
BATTERY CHARGERS	
CB10480151G	48V 15A electronic high frequency battery charger for AGM batteries
BRUS	
SZ130	N.1 PPL brush
PAD HOLDER	
TS071	N.1 pad holder
SQ. RUBBER BLADES	
KIT858	Squeegee rubber blades - front and rear blades (n.1 kit supplied as standard)