

## **BATTERY RIDE-ON SCRUBBER-DRIER**

MOD. MB 650N



## **MAIN FEATURES**

Working width 680 mm
Max. working capacity 4.000 m²/h
Solution tank capacity 150 I
Recovery tank capacity 170 I
Max. autonomy (lead-acid batteries) 4,5 h

## OTHER FEATURES AND STANDARD SUPPLY

Front wheel drive

Dirty water tank drain hose with cap Squeegee with rubber blades

Automatic on/off solution flow control electrovalve

N.2 PPL disk brushes

#### **GENERAL FEATURES**

 Speed range
 3-6 Km/h

 Max. gradient full load
 10 %

 Depression
 170 mBar

Noise level ≤ 50 dB

## DIMENSIONS AND WEIGHT

Machine length1.350 mmMachine width (squeegee not included)650 mmMachine height1.360 mmBrushes diameter2x350 mmSqueegee width870 mmMachine weight170 Kg

#### **ELECTRICAL SYSTEM**

 Voltage
 48 Volt

 Frequency
 direct current

 Vacuum motor
 750 W 48 V DC

 Brush motor
 2x450 W 48 DC

 Traction motor
 500 W 48 V DC

Recommended batteries 4 x 12V 110Ah lead-acid (C5): code 850000091 4x12V 105Ah gel (C5): code 850000070

#### **PACKAGING**

Type of packaging carton box on pallet
Dimensions 1.450x850xH1.500 mm
Volume 1,60 m³
Weight of packaging 15 Kg

### CODE DESCRIPTION

1200MB650N Battery ride-on scrubber-drier - mod. MB650N

### **BATTERY CHARGERS**

CB10480151G 48V 15A electronic high frequency battery charger for AGM batteries

# BRUSH

KIT1211 N.2 PPL brushes

# **PAD HOLDER**

KIT1205 N.2 pads holder

#### **SQ. RUBBER BLADES**

KIT1078 Squeegee rubber blades - front and rear blades (n.1 kit supplied as standard)