ARDESIA 88

PROTECTIVE PRODUCT FOR BLACK SLATE



GENERAL DESCRIPTION

ARDESIA 88 is a blend of resins, waxes and special polymers formulated for the protection of slate and black stones.

It prevents powdering and protects the surface from stains and water penetration.

ARDESIA 88 leaves a film that can be polished in order to enhance the brightness and the colour of the stone.

DIRECTION FOR USE

Sand external damaged or pulverized surfaces or wash with DEKACID or DETAR at 10%. Rinse well. Use DEKA P in case of old treatments or dirt and rinse well. For internal surfaces wash with FLUID or DEKA P to remove grease and stains. For new floors use DETAR or DEKACID at 10%. Rinse with water and let dry.

Apply **ARDESIA 88** on the floor, let dry and polish with a rotary machine equipped with a white or cream disc or a polishing machine. For floors, tables or other compact surfaces apply the first coat with **ARDESIA 88** diluted with DILUENTE B at 20-30%. For the maintenance of floors use the spray cleaning method with SPRAYCLEAN B and a rotary machine.

TECHNICAL DATA

Appearance	Dark grey liquid
Density	0.808 g/ml
Active contents	100%
Flash point	43°C

WARNINGS

Labelling



Danger

Flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes skin irritation. May cause respiratory irritation. May cause drowsiness or dizziness. Harmful to aquatic life with long lasting effects. Repeated exposure may cause skin dryness or cracking. The product is subject to ADR regulations: **UN 1263 Class 3 III** Read carefully the safety data sheet before use.



KEMIKA Spa - Sede operativa e stabilimento Via G. Di Vittorio 55 - 15076 Ovada (AL) ITALIA Tel: ++39 (0) 143 80494 – Fax. ++39 (0) 143 823068 info@kemikaspa.com - www.kemikagroup.com

