

# BASE OLIO DI LINO

IMPREGNATING PRODUCT FOR  
TERRA COTTA, WOOD AND TEAK SURFACES



## GENERAL DESCRIPTION

Linseed oil based solution used as impregnating protection for the traditional treatment of handmade terra cotta floors.  
**BASE OLIO DI LINO** can be used also for the protective treatment of Teak surfaces on boats and yachts and for the traditional treatment of wood surfaces.

## DIRECTION FOR USE

### Terra cotta floors:

Wash the floor with the deter solvent DEKA P to remove oil spots or old coats of waxes. Rinse then wash with DEKACID. Rinse, let dry the floor and then apply **BASE OLIO DI LINO** using a polish applicator or spraying it. If it is necessary, level out the product by a single disc machine equipped with red pad and spray system. Use OLEOIDRO 1 or COTTOLIQ as a final coat. Let dry the buff.

### Boats and yachts Teak surfaces:

Use NEOKLIN or ECOKLIN to remove spots and then make the acid washing using KLARITEAK to remove salts residues. Rinse and let it dry. Apply the product pure or diluted with turpentine depending on the Teak extent of absorption, using a brush or spraying it; standardize the application by a polish applicator or by the spray is method.

### Wood:

Prepare the floor by sanding it well and then apply the product using a polish applicator. Use ECOWOOD OLEO IDRO or PARKELIQ as a final coat. Let dry the buff.

## TECHNICAL DATA

Appearance	straw yellow liquid
Gravity	0.794 g/ml
Active content	100%
Flash point	38°C

## WARNINGS

### Labelling



### Danger

Flammable liquid and vapour. May be fatal if swallowed and enters airways. May cause drowsiness or dizziness. Repeated exposure may cause skin dryness or cracking.

Read carefully the safety data sheet before use.

The product is subject to ADR regulations: **UN 3265 Classe 3 III.**



KEMIKA Spa - Sede operativa e stabilimento  
Via G. Di Vittorio 55 - 15076 Ovada (AL) ITALIA  
Tel: ++39 (0) 143 80494 – Fax: ++39 (0) 143 823068  
info@kemikaspa.com - www.kemikagroup.com

