

BASYL COTTO

**SOLVENT BASED SEALER
(FOR TERRA COTTA FLOORS)**



GENERAL DESCRIPTION

BASYL COTTO is a solvent based acrylic sealer formulated to give a semigloss finish to interior and exterior terra-cotta floors. On exterior or very damp areas the terra cotta must be previously treated with the product IDROFOB C in order to hydrophobize the surface.

BASYL COTTO leaves a semigloss dry-bright film that protects from traffic marks and contrast stains penetration.

BASYL COTTO is mainly used for exterior floors.

DIRECTION FOR USE

Remove old waxes or sealers with DEKA P 10% - 20%, then wash the floor with a solution of DEKACID 10% and INDUSTRIA F 10%. Rinse well and let dry.

Apply **BASYL COTTO** on a clean and dry surface with a polish applicator or spray it evenly. Let dry and apply a second coat.

For compact floor apply the first coat diluted with 30% of DILUENTE B and 70% **BASYL COTTO**.

TECHNICAL DATA

Appearance	Light brown clear liquid
Density	0.852 g/ml
Active contents	100%
Hydrocarbon solvents	78%
Flash point	45°C

WARNINGS

In the case of baked compact verify the adhesion to use the first hand diluted with DILUENTE B (20-30%).

Labelling



Danger

Flammable liquid and vapour. May be fatal if swallowed and enters airways. May cause respiratory irritation. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects. Repeated exposure may cause skin dryness or cracking.

The product is subject to ADR regulations: **UN 1263 Class 3 III**

Read carefully the safety data sheet before use.



KEMIKA Spa - Sede operativa e stabilimento
Via G. Di Vittorio 55 - 15076 Ovada (AL) ITALIA
Tel: ++39 (0) 143 80494 - Fax: ++39 (0) 143 823068
info@kemikaspaspa.com - www.kemikaspaspa.com

