



GENERAL DESCRIPTION

CEMEN is a blend of pigments to mix with the epoxy sealer EPOSIL to produce a coloured film for the protection of concrete floors.

DIRECTION FOR USE

Mix carefully EPOSIL UNO (5 kg), EPOSIL DUE (5 kg) and CEMEN (2 kg) just immediately before use. Use the blend within 30 minutes. Apply with an sprayer and lay out with a Kanecaron 4 mm roller or apply with an airless.

When the first coat is well dried apply a second one.

A further coat of EPOSIL without coloured paste may be applied to have a more brilliant effect.

TECHNICAL DATA

Appearance	Grey paste
Active contents	70%
рН	8.5 ± 0.2
Density	1.800 g/ml
Viscosity	300 ± 100 cps

WARNINGS

Prepare the floor thoroughly with an acid wash (DEKACID + INDUSTRIA F). In the case of cements with very compact concrete and hydrophobic surface use the adhesion promoter PREPOX. Etching with a Diamond pad with abrasives grain (DIAMANT PLUS G-70) gives good results of adhesion.

The production of coloured pastes is subjected to strict controls and tests but the different lots of final product may have sligh differences in the colour shade. In order to avoid this problem, we warn to use cans from the same lot number for each surface.



KEMIKA Spa - Sede operativa e stabilimento Via G. Di Vittorio 55 - 15076 Ovada (AL) ITALIA Tel: ++39 (0) 143 80494 – Fax. ++39 (0) 143 823068 info@kemikaspa.com - www.kemikaspa.com

