# **COUNTRY OPACO**

## WATER BASED WOOD SEALER-MAT



# **GENERAL DESCRIPTION**

**COUNTRY OPACO** is a water-based emulsion of acrylic and urethanic polymers formulated as a wood floors sealer. The product is odourless, fast drying and very easy to apply. **COUNTRY OPACO** leaves a mat natural looking film resistant to scuffs and traffic marks. It shows good resistance to stains and water absorption.

COUNTRY OPACO can be also used for woodworks, cabinets and tables.

# **DIRECTION FOR USE**

For dirty or waxed floors clean with concentrated DEKA P, NEOKLIN or ECOKLIN using a floor machine equipped with an aerated black pad (Type 66). Let work and rinse with hot water, vacuuming at the same time the residues avoiding to leave the floor wet. When the floor is dry sand with a rotary machine equipped with sandpaper pad (grain 40-80-150). Apply the first coat of **COUNTRY OPACO** with a floor polish applicator, let dry and lightly sand with fine sandpaper or a special sanding disc like Sandscreen 150. Vacuum off the dust, sweep with a dump mop or a gauze, and apply a second coat.

Sand again if required and apply a final coat of COUNTRY OPACO.

# **TECHNICAL DATA**

Appearance	mat milky white liquid
рН	8.4 ± 0.2
Density	1.045 g/ml
Active contents	33%

Chemical composition - Reg. (EC) 648/2004

**Perfumes** 

## **WARNINGS**

Keep from freezing.

#### Labelling

#### Warning



May cause an allergic skin reaction. Harmful to aquatic life with long lasting effects. Read carefully the safety data sheet before use.







KEMIKA Spa - Sede operativa e stabilimento Via G. Di Vittorio 55 - 15076 Ovada (AL) ITALIA

++39 (0) 143 80494 □ info@kemikaspa.com

##+39 (0) 143 823068
www.kemikaspa.com