



CATALYST FOR IDROFOB C, IDROSTOP FLUIDO, IDROSTOP LEGANTE, OLEOIDRO 1 AND OLEOIDRO SPECIAL

GENERAL DESCRIPTION

CPI is a catalyst to be used in combination with IDROFOB C, IDROSTOP FLUIDO, IDROSTOP LEGANTE, OLEOIDRO 1 and OLEOIDRO SPECIAL in order to obtain an immediate hydrorepellent effect for these products.

CPI improves the polymerising process, allows a good penetration of the product on the surfaces and achieves a complete hydrorepellent effect within 10-12 hours.

DIRECTION FOR USE

Add 1,5 - 2% of CPI to the above mentioned products (75 - 100 grams per 5 litres of product) before using.

The mixture must be used up within a few hours, after that it loses its effect and CPI must be added again.

TECHNICAL DATA

Appearance	Transparent colourless liquid
Density	0.825 g/ml
Active contents	100%
Flash point	40°C

WARNINGS

Check that the bottle is tightly closed. Traces of humidity damage the product by gelling it.



Danger

Flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes serious eye damage. Causes skin irritation. May cause respiratory irritation. May cause drowsiness or dizziness.

The product is subject to ADR regulations: UN 1263 Class 3 III

Read carefully the safety data sheet before use.



KEMIKA Spa - Sede operativa e stabilimento Via G. Di Vittorio 55 - 15076 Ovada (AL) ITALIA Tel: ++39 (0) 143 80494 – Fax. ++39 (0) 143 823068 info@kemikaspa.com - www.kemikagroup.com

