


DE-SEC

FLOOR STRIPPER (DRY METHOD)



GENERAL DESCRIPTION

DE-SEC is a wax stripper formulated for the partial or total removal of metallized floor polishes films with the dry method.

DE-SEC used with a low-speed machine and abrasive pads removes completely the film.

DE-SEC used with a less abrasive pads, removes only partially the film and the traffic marks.

The floor cleaned with **DE-SEC** can be restored and polished again.

DE-SEC is used on floating floors or when it is not possible to wash the floor with a solution.

DIRECTIONS FOR USE

Use the product undiluted.

Total wax removal: use a rotary machine equipped with a brown aired pad and work on a small area at a time, while spraying **DE-SEC** on the floor. Change the pads when soiled. A new coat of metallized floor polish can be applied after a damp mopping or after rinsing by a mop.

Partial wax removal: use a rotary machine equipped with blue aired pad and work while spraying **DE-SEC**. Change the soiled pads.

When all traffic marks have been removed, buff with a cream pad for high speed and METALSPRAY, using the spray buffing method.

TECHNICAL DATA

Appearance	Light blue transparent liquid
pH	10.8 ± 0.2
Density	0.985 g/ml
Dry solids	1.2%
Active contents	10%

Chemical composition – Reg. (EC) 648/2004

- Non-ionic surfactants : conc. < 5%
perfumes

The product contains surfactants with primary biodegradability at least 90% and ultimate aerobic biodegradation complying with Reg. (EC) No. 648/2004.

WARNINGS

The product is not classified as dangerous.



KEMIKA Spa - Sede operativa e stabilimento
Via G. Di Vittorio 55 - 15076 Ovada (AL) ITALIA
Tel: ++39 (0) 143 80494 – Fax: ++39 (0) 143 823068
info@kemikaspa.com - www.kemikagroup.com

