


IDROSTOP LEGANTE

HYDROFOBIC PROTECTIVE COMPOSITION FOR FAÇADES



GENERAL DESCRIPTION

IDROSTOP LEGANTE is a hydrofobic sealer for outdoor walls and surfaces to be used to protect the concrete and the stones from the acid rain corrosion. The product contains silanes that react with the silicium of the wall and make a network that prevents water absorption and penetration.

IDROSTOP LEGANTE contains also acrylic polymers that have a bonding effect on the damaged material. The network of the silicium molecules allows the evaporation of the humidity with no sealing of the water inside the material. At the same time the humidity does not penetrate inside the building and the walls remain dry.

DIRECTION FOR USE

Mix the catalyst CPI at the concentration of 1.5% (75 g in 5 litres of **IDROSTOP LEGANTE**). Use the blend within 1-2 hours. Apply the product on the surface with a brush or by spraying. The surfaces must be dried and possibly cold. Avoid moments when the sun arrives on the wall. In that case the UV rays may warm up the surface and let evaporate the molecules of the silanes. A sufficient protection is achieved with 100 grams of **IDROSTOP LEGANTE** for m².

TECHNICAL DATA

Appearance	colorless liquid
Active contents	100 %
Density	0.820 g/ml
Flash point	40°C

WARNINGS

Labelling



Danger

Flammable liquid and vapour. May be fatal if swallowed and enters airways. May cause drowsiness or dizziness. Harmful to aquatic life with long lasting effects. Repeated exposure may cause skin dryness or cracking.

The effect of drowsiness and dizziness can be manifested by prolonged and repeated inhalation of the pure product.

The product is subject to ADR regulations: **UN 1263 Class 3 III**

Read carefully the safety data sheet before use.



KEMIKA Spa - Sede operativa e stabilimento
Via G. Di Vittorio 55 - 15076 Ovada (AL) ITALIA
Tel: ++39 (0) 143 80494 – Fax: ++39 (0) 143 823068
info@kemikaspa.com - www.kemikaspa.com

