

KLER

METALLIZED FLOOR POLISH



GENERAL DESCRIPTION

KLER is a metallized floor polish formulated for the maintenance of all types of floors. It is formulated using the double crosslinking technology to enhance the hardness of the film.

KLER is particularly suitable in heavy traffic areas that must be frequently waxed and as a “restorer” to repair partially damaged films of floor polish without stripping or after a partial dry stripping.

DIRECTION FOR USE

Wash the floor with a stripper like ECSTRA and rinse well. Apply two/three coats of **KLER** on a clean surface.

To restore the partially damaged film: wash with a neutral detergent like TOC then, if necessary, remove the film partially with DE SEC and a floor machine equipped with a blue pad. Damp mop to eliminate the residues. Then apply a coat of **KLER** undiluted or at 50%.

Use the high speed machine with cream pad and SPRAY NC or METALSPRAY to achieve the “wet look” gloss.

TECHNICAL DATA

Appearance	white liquid
pH	8.5 ± 0.2
Density	1.026 g/ml
Dry solids	15%
Active contents	22%
Coefficient of Friction (ASTM Method 2047/75)	0.53

WARNINGS

Contains: 2-OCTYL-2H-ISOTHIAZOL-3-ONE, 2-methylisothiazol-3(2H)-one, Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), Resin acids and Rosin acids, fumarated, esters with pentaerythritol

May produce an allergic reaction.

Keep from freezing.

The product is not classified as dangerous.



KEMIKA Spa - Sede operativa e stabilimento
Via G. Di Vittorio 55 - 15076 Ovada (AL) ITALIA
Tel: ++39 (0) 143 80494 – Fax: ++39 (0) 143 823068
info@kemikaspaspa.com - www.kemikagroup.com

