

LIQUIMAC 15

LIQUID DETERGENT FOR DISHWASHING MACHINES
(SOFT WATER)



GENERAL DESCRIPTION

Low foam liquid detergent for dishwashing machine. It is used for low hardness water (less than 15° F).

Product recommended for HACCP plan.

DIRECTION FOR USE

Dosage following water hardness

7-10° F use 0.8-1.2 g/l

10-15° F use 1.2-1.4 g/l

After a few washing cycles check the pH of the washing tank of the machine that should be 10.5-11.0 for proper washing. Increase the concentration if necessary.

For dosages controlled by a conductivity probe adjust the set-point once the pH reaches the right value.

For hardness (15-35° F) use LIQUIMAC N.F.

For hardness (over 35° F) use LIQUIMAC 80.

TECHNICAL DATA

Appearance	yellow liquid
pH	13.8 ± 0.2
Density	1.240 g/ml
Active contents	31%

Chemical composition – Reg. (EC) 648/2004

- Phosphonates : conc. < 5%

WARNINGS

Labelling



Danger

Harmful if swallowed. Causes severe skin burns and eye damage.

The product is subject to ADR regulations: **UN 1719 Class 8 PG III**

Ready carefully the safety data sheet before use



KEMIKA Spa - Sede operativa e stabilimento
Via G. Di Vittorio 55 - 15076 Ovada (AL) ITALIA
Tel: ++39 (0) 143 80494 – Fax: ++39 (0) 143 823068
info@kemikaspa.com - www.kemikagroup.com

