


# OLEOIDRO 1

OLEO-HYDROREPELLENT PROTECTIVE AGENT FOR TERRA COTTA, STONES AND CONCRETE



## GENERAL DESCRIPTION

**OLEO-IDRO 1** is a solvent based blend of oil and water repellent polymers, formulated for the protection of concrete, slate, natural stones and terracotta tiles.

**OLEOIDRO 1** prevents the penetration of stains of water based substances (wine, fruit juice, coffee, etc) as well as those of oil based substances (oil, fat, food etc.) thus making stain removal easier.

**OLEO-IDRO 1** may be used for outdoor surfaces to prevent the growth of mould and lichens. A water based detergent may be used for the maintenance of surfaces protected by **OLEOIDRO 1**.

**OLEO-IDRO 1** can be used in combination with the catalyser CPI in order to achieve immediate hydrorepellency. The product does not change the natural look of the surface.

## DIRECTION FOR USE

The surface must be clean and completely dried before the application. For terracotta floors with old treatments remove then with DEKA P at 10%-20% and then wash with DEKACID at 10%-20%. Rinse well.

Apply **OLEOIDRO 1** with a brush or spray directly onto the surface.

For a immediate hydrofobizing effect add CPI at a ratio of 75 grams of CPI for 5 litres of **OLEOIDRO 1**. Use the blend within a few days, after witch the catalyzer looses effect and must be added again.

For terracotta placed outside apply IDROFOB C before **OLEOIDRO 1**.

## TECHNICAL DATA

|                 |              |
|-----------------|--------------|
| Appearance      | clear liquid |
| Density         | 0.918 g/ml   |
| Active contents | 100%         |
| Flash point     | 45°C         |
| Viscosity       | 20 cps       |

## WARNINGS

Do not use acids on marble or other limestone.

### Labelling



### Danger

Flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness. Harmful to aquatic life with long lasting effects.

The drowsiness and dizziness effect can show for prolonged and repeated Inhalation of the product. The product is subject to ADR regulations: **UN 1263 Class III**.

Read carefully the safety data sheet before use.



KEMIKA Spa - Sede operativa e stabilimento  
Via G. Di Vittorio 55 - 15076 Ovada (AL) ITALIA

☎ ++39 (0) 143 80494  
✉ info@kemikaspaspa.com

☎ ++39 (0) 143 823068  
🌐 www.kemikaspaspa.com