PULIALKA

STRONG ALKALINE DETERGENT FOR EXTERIOR SURFACES AND TERRACOTTA FLOORS



GENERAL DESCRIPTION

PULIALKA is a strong alkaline detergent to be used for the removal of smog and black scales from façades, monuments, old buildings, churches etc.

It can be used on marble, limy stones, brick or other natural stones.

It can be used to remove oxides or paint residues from terracotta floors.

DIRECTIONS FOR USE

Apply the concentrated product with a brush or by spray on the surface previously damped. Spread evenly. Let act for at least 15 minutes, then rinse with a high pressure water hose. For floors use a rotary machine.

In case of very porous surfaces, apply **PULIALKA** and then PULIALKA GEL for a longer contact time.

Rinse very well. The first rinsing should be done with an acid solution at 3/5% of DEFOS in order to neutralize the alkaline residues. An extra rinsing with plain water is always necessary.

In case of stubborn scales on silicate stone it could be necessary to clean with PULIACID instead of DEFOS.

Cover all the aluminum frames of the windows.

PULIALKA could damage those surfaces.

TECHNICAL DATA

Appearance	Dark brown liquid
рН	14
рН 1%	12.6 ± 0.2
Density	1.261 g/ml
Active content	33%

Chemical composition - Reg. (CE) n. 648/2004

Danger

- Non-ionic surfactants

conc. 5-15%

The product contains surfactants with a minimum primary biodegradability of 90% and aerobic biodegradation in compliance with Reg. (EC) 648/2004

For more information on cleaning facades or terracotta, consult the KEMIKA workbooks.

WARNINGS



Causes severe skin burns and eye damage. The product is subject to ADR Norms: **UN 1719 Class 8 PG II.** Read carefully the safety data sheet before use.



KEMIKA Spa - Sede operativa e stabilimento Via G. Di Vittorio 55 - 15076 Ovada (AL) ITALIA Tel: ++39 (0) 143 80494 – Fax. ++39 (0) 143 823068 info@kemikaspa.com - www.kemikaspa.com

