

# SEMI-BAFF

## DRY-BRIGHT FLOOR POLISH FOR RUBBER FLOORS



### GENERAL DESCRIPTION

**SEMI-BAFF** is a metal cross-linked polish based on special flexible acrylic polymers.

Particularly suited for rubber floors, where good film flexibility is required and for soft PVC floors (gymnasiums, schools etc.). It is formulated with the double crosslinking technology that enhance the traffic resistance of the film.

### DIRECTION FOR USE

Thoroughly wash the floor with a stripping solution, then rinse.

Apply one coat of SEMI-BAFF, and a second one for a higher gloss.

SEMI-BAFF can be diluted with water to be used as a wash and wax product. SEMI-BAFF is available in different colours for rubber floors.

Traffic marks can be eliminated and the initial gloss can be restored with the spray-buffing method using a medium or high speed machine and METALSPRAY.

To clean the film use the neutral detergent TOC.

**SEMI-BAFF** is also available in the following colored versions: yellow, red, brown, blue, gray, black.

### TECHNICAL DATA

Appearance	White or colored emulsion
pH	8.3 ± 0.2
Density	1.030 g/ml
Dry solids	18%
Active contents	26%
Coefficient of friction (ASTM D 2047-75)	0.51

### WARNINGS

Contains: 2-octyl-2H-isothiazol-3-one, Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), Resin acids and Rosin acids, fumarated, esters with pentaerythritol

May produce an allergic reaction.

Keep from freezing.

The product is not classified as dangerous



KEMIKA Spa - Sede operativa e stabilimento  
Via G. Di Vittorio 55 - 15076 Ovada (AL) ITALIA  
Tel: ++39 (0) 143 80494 – Fax: ++39 (0) 143 823068  
info@kemikaspa.com - www.kemikagroup.com

