

SPLENDURO SUPER

METALLIZED POLYACRYLIC FLOOR POLISH



GENERAL DESCRIPTION

SPLENDURO SUPER is an acrylic metallized emulsion for the protection of all types of floors, mainly the porous ones.

SPLENDURO SUPER is suitable for resilient floors (PVC, rubber, linoleum, etc.), terrazzo and not polished marble floors.

The film gives a good protection against dirt, foot print and traffic marks; it gives a long lasting protection and high gloss.

It can be used also for antielectrostatic PVC floors whom it does not change the conductivity.

DIRECTION FOR USE

Application

Apply a first coat when the floor is cleaned and dry.

Apply another coat when the surface is completely dried and in any case not before 30 minutes from the moment the floor looks dry.

Maintenance

Dust-mopping and wash it with LAVACRYL or TOC. The film can be restored with the spray buffing method with METALSPRAY.

TECHNICAL DATA

Appearance	White emulsion
pH	8.9 ± 0.2
Density	1.041 g/ml
Dry solids	23%
Active content	26%
Coefficient of friction (ASTM D 2047-75)	0.54

WARNINGS

Contains: 2-OCTYL-2H-ISOTHIAZOL-3-ONE, Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), Zinc ammonia carbonate complex

May produce an allergic reaction.

Keep from freezing.

The product is not classified as dangerous.



KEMIKA Spa - Sede operativa e stabilimento
Via G. Di Vittorio 55 - 15076 Ovada (AL) ITALIA
Tel: ++39 (0) 143 80494 – Fax: ++39 (0) 143 823068
info@kemikaspa.com - www.kemikagroup.com

